



Clebo WASP-130D

1.3MEGAPIXEL 1000TVL AHD SMALLEST PINHOLE LENS CAMERA


1.3Megapixel 720P High Resolution
2D+3D DNR (Digital Noise Reduction)
D-WDR (Digital Wide Dynamic Range)
LSC (Lens Shading Compensation)
DPC (Defect Pixel Compensation)
Motion Detection
Privacy Mask
OSD Control



www.in-con.biz

Clebo WASP-130D

Demension



Specification

Clebo WASP-130D	
Image Sensor	1/3" 1.3Megapixel CMOS
Total Pixels	1312(H) x 1069(V) = 1.4M (pixels)
Effective Pixels	1305(H) x 1049(V) = 1.37M (pixels)
Scanning System	Progressive
Resolution	720P / Max. 1000TVL
Video Output	Analog HD : 720P
	Analog CVBS : 1280H NTSC/PAL
S/N Ratio	More than 50dB (AGC Off)
Min. Illumination	Color : 1.0Lux / BW : 0.5Lux /
	Color DSS : 0.002Lux / BW DSS : 0.0008Lux
Lens	Megapixel Pinhole Lens f=3.6mm
Electronic Shutter Speed	Auto / Manual (1/50(60) ~ 1/50,000sec)
Sens-up	x2 ~ x30
White Balance	ATW / AWC / Indoor / Outdoor / Manual / AWB
Auto Gain Control	0 ~ 15
BLC	Off / BLC / HSBLG
D-WDR	On / Off / Auto
Day & Night	Auto / Color / BW / EXT
2D+3D DNR	Off / Low / Middle / High
LSC	On / Off
DPC	Live DPC / White DPC / Black DPC
Defog	Off / Auto
Brightness	0 ~ 100
Sharpness	0 ~ 10
Privacy Mask	Off / On (4 area)
Motion Detection	Off / On (4 area)
Mirror	Off / Mirror / V-Flip / Rotate
Operating Temperature	-10°C ~ +50°C
Operating Humidity	30% ~ 90% RH
Power Source	DC 12V (±10%)
Power Consumption	3.6W
Dimension	38.5(W) x 37(H) x 16.5(D)mm
Weight	Appx. 100g

*Specification & Design are subject to change without prior notice

INCON

INCON Co., Ltd. Mario Tower 7F, 28, Digital-ro 30-gil, Guro-gu, Seoul, Korea, 152-050
 Tel:+82-2-558-9130, +82-31-455-8600 Email : sales@in-con.biz www.in-con.biz