

DVR9000 Series

High Quality Picture


Real-Time Live Display
Hardware based H.264
Hybrid option
Pentaplex
Intuitive User-friendly interface
Multi-scenario
Event-driven Recording schedule



High Quality Picture

DVR9000 Series

Demension



Specification

NetSafe DVR9116	
General	
Video Format	NTSC/PAL
Video Input	16BNC
	1 VGA
Video Output	16 BNC (Loop)
	1CH CCTV Out (4CH Optional)
Display Mode	1,4,7,9,10,13,16 Sequecce
Display speed	Real-Time Live Display
Recording Resolution	720x480/720x240/360x240 (NTSC) / 720X576/720X288/ 360X288 (PAL)
Audio In/Out	16RCA/1RCA
Alarm In/Out	16/16
Detailed Spec.	
Recording Rate	480fps /400fps (@D1)
Compression Type	Enhanced H.264
Operating System	Microsoft Window 7 Embedded
Storage	Built-in 500GB (Up to 6HDDs), DVD-RW
Backup Interface	DVD-RW,USB memory, External HDD/ODD, Network Backup
Backup Format	Backup Viewer(Exclusive File Format)-Export in AVI, JPEG
Network Connection	Gigabit Ethernet(10/100/1000Mbps)
RS232	POS/ATM or External Keyboard Controller
RS485/422	PTZ control or External Keyboard Controller
USB	USB 2.0 (480Mbps)
Additional Functions	
Recording Mode	Event-Driven (Motion,Sensor), Schedule, Instant, Intensive Recording
Search Mode	Backup ,Preview, Object, Index, Bookmark, Panorama(Optional), POS (optional)
Motion Detection	Motion detection Areas and Sensitivity Setting
Tolerance	Watchdog, External UPS (Optional)
Water mark	Support
Two-away Audio	Support
Others	Remote S/W,(Remote, iDVR, Emergency Agent),Backup Viewer,Image Cleaning, SYNC
Dimension & Environment	
Dimension (W x H x D)	440mm x 177mm x 550mm (4U)
Weight	20kg
Operating Temperature	5℃~40℃
Humidity	10~80%
Power Requirement	100V~240V AC
Power consumption	130W

*Specification & Design are subject to change without prior notice

Incon

INCON Co., Ltd. Mario Tower 7F, 28, Digital-ro 30-gil, Guro-gu, Seoul, Korea, 152-050
Tel:+82-2-558-9130, +82-31-455-8600 Email : sales@in-con.biz www.in-con.biz