



Clebo MB721M4TIR

x5 2.0M Full-HD IP PTZ Outdoor Flat Dome


Real-time High Definition Bullet Camera
Triple codec, Simultaneous Multi Streaming
Local SD Card Backup
Day & Night by ICR
POE (Power over Ethernet)
Weather Proof Design



www.in-con.biz

Clebo MB721M4TIR

Demension



Specification

Clebo MB721M4TIR	
VIDEO	
Image Sensor	1/2.8 Sony 'Exmor' CMOS
Total Pixels	2000(H)X1241(V)
Effective Pixels	1920(H)X1080(V)
Resolution	1080p (2.1 Megapixels)
Scanning System	Progressive
Minimum Illumination @ 30IRE	Color : 2.4 Lux @ F2.0, 30 IREB/W : 0.5 Lux @ F2.0, 30 IRE
Minimum Illumination @ 50IRE	Color : 4.0 Lux @ F1.6, 50 IREB/W : 0.8 Lux @ F1.6, 50 IRE
IR LED & Range	24 IR LED up to 50ft "Smart IR On / Off"
LED Saturation	OK
S/N Ratio	More than 50 dB
Video Output	N/A
LENS	
Focal Length	4 mm
Max. Aperture Ratio	F1.8 fixed
Zoom	12x Digital
Focus Control	Manual
Lens Type	Manual Fixed
Mount Type	M12
Angle of View	H: 86°
Adjustment Range	Pan:0°~355°, Tilt: 0°~90°, Rotate: 0°~350°
Pan / Tilt Speed	N/A
Preset	N/A
Pattern	N/A
Group	N/A
Scan	N/A
Camera Features	
Wide Dynamic Range	True WDR
Dynamic Range dBs	100dB
Day / Night	True Day/Night (ICR), Color, B/W, External
Backlight Compensation	Off / BLC / HLC / WDR
Digital Noise Reduction	Low/Middle/High
Digital Slow Shutter	Off / 2x ~ 8x
White Balance	Auto, Auto-Ext. Indoor, Outdoor, Manual, One-Push"set-up"Mode
Auto White Balance Range	2,000 ~ 11,000K
Shutter Speed	1/30~1/60,000 sec.
Auto Gain Control	0dB ~ 41dB
Privacy Masking	16 Zones
Mirror / Flip	On / OFF
Defog	On / OFF
Network	
Video Compression Type	H.264 Profiles: High, main, Base MJPEGMpeg4: Simple profile
Streaming Capability	2 Profiles
Streaming Mode	Unicast / Multicast
Max. User Access	up to 6 users at Unicast Mode
Video Quality Adjustment	H.264: Quality, CBR(Bitrate Mode/Target Bitrate)MJPEG: Image Treaster
Audio Streaming	N/A
Audio Compression	N/A
Audio In / Out	N/A
Audio Control	Input Gain, Output Volume
Alarm In / Out	N/A
Alarm Triggers	Off, Always, Activation Schedule
Alarm Action	Notification via Email or Onvif or RTP metadata
Local Storage	Support "Network Loss Emergency Recording" and "Remote Backup" per schedule(Continuous, Motion)Pre/ motion post/ post alarm recording(5sec.)
(Micro SD / MicroSDHC up to 32GB class10)	
Supported Protocols	IPv4/IPv6, TCP/IP, RTP Multicast, HTTP, DHCP, PPPoE, ICMP, ARP, RARP, RTSP, NTP, SNMP, SMTP, FTP, UPnP, DNS, DDNS
Security	HTTP Login Authentication (unique or public certificate), IP Address Filtering
ONVIF Conformance	Profile S
Web Viewer	Supported OS: Windows XP, Vista, 7, MAC OSSupported Browser: Internet Explorer 7.0 or higher, Chrome, Firefox, Safari"
Mobile Viewer	TBD
CMS/VMS	TBD
General	
Input Voltage	12vDC / PoE (802.3af class 2 Max. 12.94W)
Power Consumption (W)	3.5W(IR Off) / 5W (IR on)
Operating Temperature	-30°C ~ 55°C (-22°F ~ 131° F)
Active/Passive Cooling	Passive
Rated Amperage	300mA (IR Off)/ 430mA(IR on)
IP Rating	IP66
Dimensions	H: 74.3mm W: 125mm
Weight	400 g
Approvals	FCC, CE, ROHS, IP66

*Specification & Design are subject to change without prior notice

INCON

INCON Co., Ltd. Mario Tower 7F, 28, Digital-ro 30-gil, Guro-gu, Seoul, Korea, 152-050

Tel:+82-2-558-9130, +82-31-455-8600 Email : sales@in-con.biz www.in-con.biz