

# NetSafe DVR 9116

## High Quality Picture



### About

Netsafe 9000 series is premier PC DVR based on cutting-edge H,264 compression supporting all channel real-time live view and recording at D1. It also allows for multiple client access, providing complete remote control of numerous third party PTZ cameras, various digital searches and most DVR functions and setup.

### Key Feature

- Real-Time Live Display
- 480FPS/400FPS(@D1,NTSC/PAL)Recording
- Hardware based H,264
- Hybrid option
- Pentaplex
- Intuitive User-friendly interface
- In-live Search
- System Auto-recovery (H/W watchdog)
- Support Numerous 3rd party devices
- Multi-scenario/ Event-driven Recording schedule
- Two-way audio

### Specification

General	NetSafe DVR9116
Video Format	NTSC/PAL
Video Input	16BNC
Video Output	1 VGA
	16 BNC (Loop)
	1CH CCTV Out (4CH Optional)
Display Mode	1, 4, 7, 9, 10, 13, 16 Sequecce
Display speed	Real-Time Live Display
Recording Resolution	720x480/720x240/360x240 (NTSC) / 720X576/720X288/ 360X288 (PAL)
Audio In/Out	16RCA/1RCA
Alarm In/Out	16/16

Detailed Spec.	
Recording Rate	480fps /400fps (@D1)
Compression Type	Enhanced H,264
Operating System	Microsoft Window 7 Embedded
Storage	Built-in 500GB (Up to 6HDDs), DVD-RW
Backup Interface	DVD-RW,USB memory, External HDD/ODD, Network Backup
Backup Format	Backup Viewer(Exclusive File Format)-Export in AVI, JPEG
Network Connection	Gigabit Ethernet(10/100/1000Mbps)
RS232	POS/ATM or External Keyboard Controller
RS485/422	PTZ control or External Keyboard Controller
USB	USB 2,0 (480Mbps)

Additional Functions	
Recording Mode	Event-Driven (Motion,Sensor), Schedule, Instant, Intensive Recording
Search Mode	Backup ,Preview, Object, Index, Bookmark, Panorama(Optional), POS (optional)
Motion Detection	Motion detection Areas and Sensitivity Setting
Tolerance	Watchdog, External UPS (Optional)
Water mark	Support
Two-away Audio	Support
Others	Remote S/W,(Remote, iDVR, Emergency Agent),Backup Viewer, Image Cleaning, SYNC

Dimension & Environment	
Dimension (W x H x D)	440mm x 177mm x 550mm (4U)
Weight	20kg
Operating Temperature	5℃ ~40℃
Humidity	10~80%
Power Requirement	100V~240V AC
Power consumption	130W

### Software

- Mobile Remote Viewer ( iPhone, Android )
- NxMS software (CMS)

### Dimension

